

Sun Chemical Corporation 2642 State Rd. 28W


FRANKFORT USA

IN 46041



000013

PROGRESS PRINTING COMPANY 2677 WATERLICK ROAD LYNCHBURG, VA 24502 USA



Save Money! Be Green! Receive MSDS electronically! Email your request to regulatory.emsds@sunchemical.com

Ayez une pensée pour l'environnement ! Gagnez du temps et de l'argent ! Recevez vos FDS par voie électronique! Envoyez vos demandes à regulatory.emsds@sunchemical.com

Ahorra dinero! Cuida el medio ambiente! Recibe las Hojas de Seguridad por correo electrónico! Envoyez vos demandes a regulatory.emsds@sunchemical.com

Sparen Sie Geld! Handeln Sie umweltbewußt! Fordern Sie Sicherheitsdatenblätter in elektronischer Form an. Richten Sie Ihre E-Mail an: regulatory.emsds@sunchemical.com

Risparmia soldi! Sii ecologico! Ricevi MSDS in formato elettronico! Invia la tua richiesta all'indirizzo regulatory.emsds@sunchemical.com

Poupe dinheiro! Seja verde! Receba as F.D.S. electronicamente! Envie o seu pedido para o email regulatory.emsds@sunchemical.com

Sun Chemical Corporation 2642 State Rd. 28W FRANKFORT

USA

IN 46041



000014

PROGRESS PRINTING COMPANY 2677 WATERLICK ROAD LYNCHBURG, VA 24502 USA

February 16, 2023

Save Money! Be Green! Receive MSDS electronically! Email your request to regulatory.emsds@sunchemical.com

Ayez une pensée pour l'environnement ! Gagnez du temps et de l'argent ! Recevez vos FDS par voie électronique! Envoyez vos demandes à regulatory.emsds@sunchemical.com

Ahorra dinero! Cuida el medio ambiente! Recibe las Hojas de Seguridad por correo electrónico! Envoyez vos demandes a regulatory.emsds@sunchemical.com

Sparen Sie Geld! Handeln Sie umweltbewußt! Fordern Sie Sicherheitsdatenblätter in elektronischer Form an. Richten Sie Ihre E-Mail an: regulatory.emsds@sunchemical.com

Risparmia soldi! Sii ecologico! Ricevi MSDS in formato elettronico! Invia la tua richiesta all'indirizzo regulatory.emsds@sunchemical.com

Poupe dinheiro! Seja verde! Receba as F.D.S. electronicamente! Envie o seu pedido para o email regulatory.emsds@sunchemical.com



SAFETY DATA SHEET

Section 1. Identification

Product code

: FFFWH4182782/K390

GHS product identifier

WOHS PROCESS YELLOW

Relevant identified uses of the substance or mixture and uses advised against

Printing ink; Printing ink related material; Colorant

Manufacturer / Distributor

: Sun Chemical Corporation North American Inks 135 West Lake Street Northlake, IL 60164 US: +1 708 236 3798

Emergency telephone

number (with hours of operation)

Other information e-mail address of person responsible for this SDS

+1 (800) 424-9300 (U.S.) (24 hours)

+1 (703) 527-3887 (International) (24 hours)

: +1 708 236 3798

: regulatory.affairs@sunchemical.com

Section 2. Hazards identification

OSHA/HCS status

While this material is not considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200), this SDS contains valuable information critical to the safe handling and proper use of the product. This SDS should be retained and available for employees and other users of this product.

Classification of the substance or mixture

: Not classified.

GHS label elements

Signal word

: No signal word.

Hazard statements

: No known significant effects or critical hazards.

Precautionary statements

Prevention Response

: Not applicable. : Not applicable. : Not applicable.

Storage Disposal

: Not applicable.

Hazards not otherwise

: None known.

classified

Section 3. Composition/information on ingredients

Substance/mixture

: Mixture

CAS number/other identifiers

16- February- 2023 en - US Page: 1/9

Section 3. Composition/information on ingredients

Section 3. Composition/Information	CAS number	%
Ingredient name Petroleum Middle Distillate Hydrotreated Middle Distillate	64741-44-2 64742-46-7 64741-44-2 64742-53-6	10 - 20 5 - 10 5 - 10 5 - 10
Petroleum Middle Distillate Severely Treated Light Naphthenic Distillate	to due to batch variation.	

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact

: Remove contact lenses, if present and easy to do. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open.

Inhalation

: Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained

Skin contact

: Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.

Ingestion

: If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do not induce vomiting.

Most important symptoms/effects, acute and delayed

Potential acute health effects

Eye contact

: No known significant effects or critical hazards.

Inhalation

: No known significant effects or critical hazards.

Skin contact Ingestion

: No known significant effects or critical hazards. : No known significant effects or critical hazards.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician

: In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

Specific treatments

: No specific treatment.

Protection of first-aiders

: No action shall be taken involving any personal risk or without suitable training.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

Suitable extinguishing

: Use dry chemical, CO2, water spray (fog) or foam.

media

Unsuitable extinguishing media

: Do not use water jet.

Specific hazards arising from the chemical

: In a fire or if heated, a pressure increase will occur and the container may burst.

Hazardous thermal decomposition products : Decomposition products may include the following materials:

carbon dioxide carbon monoxide nitrogen oxides

halogenated compounds

Section 5. Fire-fighting measures

Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters Remarks

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: Avoid breathing vapor or mist. Refer to protective measures listed in sections 7 and 8.

For emergency responders : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-

Environmental precautions

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

Small spill

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

Protective measures

: Keep container tightly closed. Avoid contact with skin and eyes. Always keep in containers made from the same material as the original one. Avoid breathing dust. Avoid inhalation of vapor, spray or mist. Put on appropriate personal protective equipment (see Section 8). Never use pressure to empty. Container is not a pressure vessel. Comply with the health and safety at work laws.

Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in a dry, cool and well-ventilated area. Keep away from heat and direct sunlight. Keep container tightly closed. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Use appropriate containment to avoid environmental contamination. Do not reuse container. See Section 10 for incompatible materials before handling or use.

Remarks:

Materials such as cleaning rags, paper wipes and protective clothing, which are contaminated with the product may spontaneously self-ignite some hours later. To avoid the risks of fires, all contaminated materials should be stored in purpose-built containers or in metal containers with tight-fitting, self-closing lids. Contaminated materials should be removed from the workplace at the end of each working day and be stored outside. (Soybean oil)

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Occupational exposure limits	Exposure limits		
Ingredient name	NIOSH REL (United States, 10/2016).		
Hydrotreated Middle Distillate	TWA: 5 mg/m³ 10 hours. Form: Mist STEL: 10 mg/m³ 15 minutes. Form: Mist ACGIH TI V (United States, 3/2019).		
Severely Treated Light Naphthenic Distillate	TWA: 5 mg/m³ 8 hours. Form: Inhalable fraction NIOSH REL (United States, 10/2016). TWA: 5 mg/m³ 10 hours. Form: Mist STEL: 10 mg/m³ 15 minutes. Form: Mist OSHA PEL (United States, 5/2018). TWA: 5 mg/m³ 8 hours.		

Appropriate engineering controls

Environmental exposure controls

: Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eve/face protection

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-

Skin protection

Hand protection

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is

Body protection

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection

In case of inadequate ventilation wear respiratory protection. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Use a properly fitted, air-purifying or airfed respirator complying with an approved standard if a risk assessment indicates this is necessary.

Section 9. Physical and chemical properties

Appearance

Physical state Color

: Liquid.

Odor

: Yellow. Characteristic.

Odor threshold

: Not applicable.



Section 9. Physical and chemical properties

: Not tested Melting point : Not available.

Boiling point : Lowest known value: 100°C (212°F) Flash point : Lowest known value: >93.3°C (200°F) **Evaporation rate**

: Highest known value: <1 (Hydrotreated Middle Distillate) Weighted average: 0.9compared with butyl acetate

Flammability (solid, gas) : Not available. Lower and upper explosive : Not tested

(flammable) limits

Vapor pressure : Not available. Vapor density : Not tested

Density : 1 g/cm³ (8.349 lbs/gal)

Solubility : Not tested Partition coefficient: n-

octanol/water

: Not applicable.

Auto-ignition temperature : Not applicable. Decomposition temperature : Not applicable.

Viscosity

: Kinematic (40°C): >0.205 cm²/s (>20.5 cSt)

VOC

VOC % by W/W : 39.8 VOC % by V/V : 47.5 VOC Lbs./Gallon : 3.3 VOC Lbs./Gallon without : 3.5

Water and exempt

solvents

Section 10. Stability and reactivity

Reactivity : No specific test data related to reactivity available for this product or its ingredients.

Chemical stability : The product is stable.

Possibility of hazardous

reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

Conditions to avoid : No specific data.

Incompatible materials : No specific data.

Hazardous decomposition

products

: Under normal conditions of storage and use, hazardous decomposition products should

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

The product has not been tested.

Conclusion/Summary : Procedure used to derive the classification: Calculation method.

Irritation/Corrosion

The product has not been tested.

16- February- 2023 en - US Page: 5/9

Section 11. Toxicological information

Sensitization

The product has not been tested.

Mutagenicity

The product has not been tested.

Conclusion/Summary

: Procedure used to derive the classification: Calculation method.

Carcinogenicity

The product has not been tested.

Conclusion/Summary

: Procedure used to derive the classification: Calculation method.

Reproductive toxicity

The product has not been tested.

Conclusion/Summary

: Procedure used to derive the classification: Calculation method.

Teratogenicity

The product has not been tested.

Conclusion/Summary

: Procedure used to derive the classification: Calculation method.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard	Result
Name Petroleum Middle Distillate	ASPIRATION HAZARD - Category 1 ASPIRATION HAZARD - Category 1
Hydrotreated Middle Distillate Petroleum Middle Distillate Severely Treated Light Naphthenic Distillate	ASPIRATION HAZARD - Category 1 ASPIRATION HAZARD - Category 1

Information on the likely

: Not available.

routes of exposure

Potential acute health effects

Eye contact

: No known significant effects or critical hazards.

Inhalation

: No known significant effects or critical hazards. : No known significant effects or critical hazards.

Skin contact Ingestion

: No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact

: No specific data.

Inhalation

: No specific data.

Skin contact Ingestion

: No specific data. : No specific data.

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate

: Not available.

effects

Potential delayed effects

: Not available.

Long term exposure

Potential immediate

: Not available.

effects

Section 11. Toxicological information

Potential delayed effects : Not available.

Potential chronic health effects

General : No known significant effects or critical hazards.

Carcinogenicity : No known significant effects or critical hazards.

Mutagenicity : No known significant effects or critical hazards.

Teratogenicity : No known significant effects or critical hazards.

Developmental effects : No known significant effects or critical hazards.

Fertility effects : No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Oral	ATE value	Service de la constitución de la
Dermal Inhalation (dusts and mists)	6091.62 mg/kg 13401.56 mg/kg 18.27 mg/l	

Section 12. Ecological information

Toxicity

The product has not been tested.

Conclusion/Summary : Procedure used to derive the classification: Calculation method.

Persistence and degradability

The product has not been tested.

Conclusion/Summary : Procedure used to derive the classification: Calculation method.

Bioaccumulative potential

Not available.

Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

Other adverse effects

: No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and

Section 14. Transport information

ection 14.	DOT Classification	TDG Classification	Mexico Classification	IMDG	IATA
UN number					
UN proper shipping name			Not regulated.	Not regulated.	Not regulated.
Transport hazard class(es)	Not regulated.	Not regulated.	Not regulated.	, total g	
			-	-	-
Packing group	-	-	1.1	No.	No.
Environmental hazards	No.	No.	No.	110.	-
Additional information	-	-	-	-	

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Section 15. Regulatory information

TSCA 8(b) inventory

: Listed

U.S. Federal regulations

: TSCA 5(a)2 proposed significant new use rule (SNUR):

Nonyl Phenol

25154-52-3

TSCA 8(a) PAIR: Dipropylene Glycol Monobutyl Ether; Nonyl Phenol; naphthalene Clean Water Act (CWA) 307: Ethyl Benzene; benz[a]anthracene; naphthalene Clean Water Act (CWA) 311: Ethyl Benzene; xylene; naphthalene; propylene oxide

ARA 313		CAS number	%
	Product name	CAS number	70
Supplier notification	None identified.		
Supplier notification			

Toxics in Packaging

(CONEG)

: In compliance.

State regulations

Massachusetts

: The following components are listed: Hydrotreated Middle Distillate (64742-46-7),

Severely Treated Light Naphthenic Distillate (64742-53-6), Clay (1332-58-7)

New York

New Jersey

: The following components are listed: Hydrotreated Middle Distillate (64742-46-7), Clay

(1332-58-7)

Pennsylvania

: The following components are listed: Soybean oil (8001-22-7), Clay (1332-58-7)

Canada inventory

: All components are listed or exempted.

International regulations

Section 15. Regulatory information

International lists

: Australia inventory (AIIC): Not determined. China inventory (IECSC): Not determined.

Japan inventory (CSCL): At least one component is not listed. Korea inventory (KECI): All components are listed or exempted.

New Zealand Inventory of Chemicals (NZIoC): At least one component is not listed.

Philippines inventory (PICCS): At least one component is not listed. Taiwan Chemical Substances Inventory (TCSI): Not determined.

Turkey inventory: At least one component is not listed.

Europe Inventory: Please contact your supplier to get the information.

Section 16. Other information

National Fire Protection Association (U.S.A.)

Flammability Health Special

Reprinted with permission from NFPA 704-2001, Identification of the Hazards of Materials for Emergency Response Copyright ©1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the National Fire Protection Association, on the referenced subject which is represented only by the standard in its entirety.

Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

History

Date of issue/Date of

revision

: 2/6/2023

Date of previous issue

: 1/10/2023

Version

: 2.02

Key to abbreviations

: ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor

Instability/Reactivity

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973

as modified by the Protocol of 1978. ("Marpol" = marine pollution)

UN = United Nations

References

: Not available.

Indicates information that has changed from previously issued version.

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. FFFWH2182783

VOLATILE CHEMICALS REPORT

	VOLATILE CITEMIONES IN	
		US EPA Designate
A. Product Density 1.) 1 g/cm³ (8	/: 3.349 lbs/gal)	=(Dc)s
2) 48.	ntent: 2 Weight percent of nonvolatiles in product 5 Volume percent of nonvolatiles in product 6 Density, lb nonvolatiles/gal nonvolatiles	=(Wn)s =(Vn)s =(Dn)s
C. Volatiles: 1.) 43. 2.) 7	8 Weight percent of total volatiles in product 1 Density, lb volatiles/gal volatiles	=(Wv)s =(Dv)s
D. Water Conten 1.) 0 2.) 0	t: .0 Weight percent of water in product .0 Volume percent of water in product	=(Ww)s =(Vw)s
1.) 39 2.) 47 3.) 6.5	nic Compounds, (VOCs): 1.8 Weight percent of organic volatiles in product 7.5 Volume percent of organic volatiles in product 99 Density, Ib organic volatiles/gal organic volatiles 1.8 Weight percent of VOCs in total volatiles 2.2 Volume percent of VOCs in total volatiles	=(Wo)s =(Vo)s =(Do)s =(Wo)v =(Vo)v
1.) a.) 398. 2.) a.) 414. 2.) c.) 4	in Product Expressed in Other Terms: 3.3 lb VOC / gal Product .18 grams VOC / liter Product 3.5 lb VOC / gal Product less water & exempt solvent .77 grams VOC / liter Product less water & exempt solvent 1.5 Weight percent of organic volatiles (VOC) in Product less water & exempt solvents. 6.8 lb VOC / gal total nonvolatiles	

1/2

0	11-		1000
G.	VO	lati	les

S number % by weight Density (lb/g
742-46-7 9.77 7.17 741-44-2 8.21 6.8 742-53-6 7.36 7.34 711-28-2 0.8 7.65 742-47-8 0.11 6.59 to 6.84 742-53-6 0.35 7.37 0.06 8.34 0.03 7.37 4 8.34

The US EPA definition of VOC does not include water, ammonia or other exempt substances. The VOC values reported are based on current formulations and supplier data.

This report also serves as a Certified Product Data Sheet (CPDS) as defined by 40 CFR 63 National Emissions Standard for HAPS, Subpart KK for the Printing Industry

			100