

# SAFETY DATA SHEET

## 1. Identification

**Product number** U-135A  
**Product Identifier** **U-135A HI-P CONTACT CLEANER**  
**Revision date** 03-06-2017  
**Company information** UNIVERSAL  
PO Box 15127  
St. Louis MO 63110 United States  
**Company phone** General Assistance 800-325-4859  
**Emergency telephone US** 1-800-255-3924 Chem-Tel  
**Emergency telephone outside US**  
**Version #** 08  
**Supersedes date** 10-10-2016  
**Recommended use** CLEANER  
**Recommended restrictions** None known.

## 2. Hazard(s) identification

**Physical hazards** Flammable aerosols Category 1  
**Health hazards** Skin corrosion/irritation Category 2  
Reproductive toxicity Category 2  
Specific target organ toxicity, single exposure Category 3 narcotic effects  
Specific target organ toxicity, repeated exposure Category 2  
Aspiration hazard Category 1  
**OSHA defined hazards** Not classified.

### Label elements



### Signal word

Danger

### Hazard statement

Extremely flammable aerosol. May be fatal if swallowed and enters airways. Causes skin irritation. May cause drowsiness or dizziness. Suspected of damaging fertility or the unborn child. May cause damage to organs through prolonged or repeated exposure.

### Precautionary statement

#### Prevention

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not breathe gas. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face protection.

#### Response

If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. If on skin: Wash with plenty of water. If inhaled: Remove person to fresh air and keep comfortable for breathing. If exposed or concerned: Get medical advice/attention. Call a poison center/doctor if you feel unwell. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse. Collect spillage.

#### Storage

Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

#### Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations.

### Environmental hazards

Hazardous to the aquatic environment, acute hazard Category 2

	Hazardous to the aquatic environment, long-term hazard	Category 2
Hazard(s) not otherwise classified (HNOC)	None known.	
Supplemental information	None.	

### 3. Composition/information on ingredients

#### Mixtures

Chemical name	Common name and synonyms	CAS number	%
Naphtha, (Petroleum), Hydrotreated Light		64742-49-0	40 - 60
1,1-Difluoroethane		75-37-6	20 - 40
n-Hexane		110-54-3	20 - 40
Isopropyl Alcohol		67-63-0	2.5 - 10
Cyclohexane		110-82-7	0.1 - 1
Other components below reportable levels			0.01 - 0.1

\*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

### 4. First-aid measures

<b>Inhalation</b>	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
<b>Skin contact</b>	Remove contaminated clothing. Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.
<b>Eye contact</b>	Rinse with water. Get medical attention if irritation develops and persists.
<b>Ingestion</b>	Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.
<b>Most important symptoms/effects, acute and delayed</b>	Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness and dizziness. Headache. Nausea, vomiting. Skin irritation. May cause redness and pain. Prolonged exposure may cause chronic effects.
<b>Indication of immediate medical attention and special treatment needed</b>	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
<b>General information</b>	IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.

### 5. Fire-fighting measures

<b>Suitable extinguishing media</b>	Foam. Powder. Carbon dioxide (CO2).
<b>Unsuitable extinguishing media</b>	Do not use water jet as an extinguisher, as this will spread the fire.
<b>Specific hazards arising from the chemical</b>	Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.
<b>Special protective equipment and precautions for firefighters</b>	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
<b>Fire fighting equipment/instructions</b>	Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.
<b>Specific methods</b>	Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. In the event of fire and/or explosion do not breathe fumes.
<b>General fire hazards</b>	Extremely flammable aerosol.

## 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not breathe gas. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

### Methods and materials for containment and cleaning up

Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Prevent entry into waterways, sewer, basements or confined areas. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

### Environmental precautions

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

## 7. Handling and storage

### Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Do not breathe gas. Avoid contact with eyes, skin, and clothing. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices.

### Conditions for safe storage, including any incompatibilities

Level 3 Aerosol.

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store away from incompatible materials (see Section 10 of the SDS).

## 8. Exposure controls/personal protection

### Occupational exposure limits

#### US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value
Cyclohexane (CAS 110-82-7)	PEL	1050 mg/m <sup>3</sup>
Isopropyl Alcohol (CAS 67-63-0)	PEL	300 ppm 980 mg/m <sup>3</sup>
n-Hexane (CAS 110-54-3)	PEL	400 ppm 1800 mg/m <sup>3</sup> 500 ppm

#### US. ACGIH Threshold Limit Values

Components	Type	Value
Cyclohexane (CAS 110-82-7)	TWA	100 ppm
Isopropyl Alcohol (CAS 67-63-0)	STEL	400 ppm
n-Hexane (CAS 110-54-3)	TWA	200 ppm
	TWA	50 ppm

#### US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value
Cyclohexane (CAS 110-82-7)	TWA	1050 mg/m <sup>3</sup>

**US. NIOSH: Pocket Guide to Chemical Hazards**

Components	Type	Value
Isopropyl Alcohol (CAS 67-63-0)	STEL	300 ppm 1225 mg/m <sup>3</sup>
	TWA	500 ppm 980 mg/m <sup>3</sup>
n-Hexane (CAS 110-54-3)	TWA	400 ppm 180 mg/m <sup>3</sup> 50 ppm

**US. Workplace Environmental Exposure Level (WEEL) Guides**

Components	Type	Value
1,1-Difluoroethane (CAS 75-37-6)	TWA	2700 mg/m <sup>3</sup> 1000 ppm

**Biological limit values**

**ACGIH Biological Exposure Indices**

Components	Value	Determinant	Specimen	Sampling Time
Isopropyl Alcohol (CAS 67-63-0)	40 mg/l	Acetone	Urine	*
n-Hexane (CAS 110-54-3)	0.4 mg/l	2,5-Hexanedione, without hydrolysis	Urine	*

\* - For sampling details, please see the source document.

**Exposure guidelines**

**US - California OELs: Skin designation**

n-Hexane (CAS 110-54-3) Can be absorbed through the skin.

**US ACGIH Threshold Limit Values: Skin designation**

n-Hexane (CAS 110-54-3) Can be absorbed through the skin.

**Appropriate engineering controls**

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.

**Individual protection measures, such as personal protective equipment**

**Eye/face protection** Wear safety glasses with side shields (or goggles).

**Skin protection**

**Hand protection** Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove supplier.

**Other** Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

**Respiratory protection** If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator.

**Thermal hazards** Wear appropriate thermal protective clothing, when necessary.

**General hygiene considerations**

Observe any medical surveillance requirements. When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

**9. Physical and chemical properties**

**Appearance**

**Physical state** Gas.  
**Form** Aerosol.  
**Color** Not available.

**Odor** Not available.

**Odor threshold** Not available.

**pH** Not available.

Melting point/freezing point	Not available.
Initial boiling point and boiling range	Not available.
Flash point	-58.0 °F (-50.0 °C) Propellant estimated
Evaporation rate	Not available.
Flammability (solid, gas)	Not available.
<b>Upper/lower flammability or explosive limits</b>	
Flammability limit - lower (%)	3.9 % estimated
Flammability limit - upper (%)	13.2 % estimated
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	40 - 50 psig @70F estimated
Vapor density	Not available.
Relative density	Not available.
<b>Solubility(ies)</b>	
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	611.6 °F (322 °C) estimated
Decomposition temperature	Not available.
Viscosity	Not available.
<b>Other information</b>	
Explosive properties	Not explosive.
Oxidizing properties	Not oxidizing.
Specific gravity	0.673 - 0.693 estimated

## 10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	Hazardous polymerization does not occur.
Conditions to avoid	Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Acids. Strong oxidizing agents. Isocyanates. Chlorine.
Hazardous decomposition products	No hazardous decomposition products are known.

## 11. Toxicological information

### Information on likely routes of exposure

Inhalation	May cause damage to organs through prolonged or repeated exposure by inhalation. May cause drowsiness and dizziness. Headache. Nausea, vomiting.
Skin contact	Causes skin irritation.
Eye contact	Direct contact with eyes may cause temporary irritation.
Ingestion	Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.

**Symptoms related to the physical, chemical and toxicological characteristics**      Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness and dizziness. Headache. Nausea, vomiting. Skin irritation. May cause redness and pain.

### Information on toxicological effects

**Acute toxicity**      May be fatal if swallowed and enters airways. Narcotic effects.

Product	Species	Test Results
11 OZ U-135A HI P LB 12PK		
<b>Acute</b>		
<b>Dermal</b>		
LD50	Rat	7082 mg/kg
<b>Inhalation</b>		
LC50	Rat	806 mg/l/4h
<b>Components</b>		
Cyclohexane (CAS 110-82-7)		
<b>Acute</b>		
<b>Dermal</b>		
LD50	Rabbit	> 2000 mg/kg
<b>Inhalation</b>		
LC50	Rat	> 32880 mg/m3, 4 Hours
		> 5540 ppm, 4 Hours
<b>Oral</b>		
LD50	Rabbit	> 5000 mg/kg
	Rat	> 5000 mg/kg
Isopropyl Alcohol (CAS 67-63-0)		
<b>Acute</b>		
<b>Dermal</b>		
LD50	Rabbit	16.4 ml/kg, 24 Hours
<b>Inhalation</b>		
LC50	Rat	> 10000 ppm, 6 Hours
<b>Oral</b>		
LD50	Rat	5.84 g/kg
Naphtha, (Petroleum), Hydrotreated Light (CAS 64742-49-0)		
<b>Acute</b>		
<b>Dermal</b>		
LD50	Guinea pig; Rabbit	> 9.4 ml/kg, 24 Hours
	Rabbit	> 1900 mg/kg, 24 Hours
<b>Inhalation</b>		
LC50	Rat	> 5000 mg/m3, 4 Hours
		> 4980 mg/m3
		> 4980 mg/m3, 4 Hours
		> 4.96 mg/l, 4 Hours
		13700 ppm, 4 Hours
<b>Oral</b>		
LD50	Rat	4820 mg/kg
n-Hexane (CAS 110-54-3)		
<b>Acute</b>		
<b>Dermal</b>		
LD50	Rabbit	> 2000 mg/kg, 4 Hours
		> 5 ml/kg, 4 Hours
<b>Inhalation</b>		
LC50	Rat	> 5000 ppm, 24 Hours
		> 31.86 mg/l
		73860 ppm, 4 Hours
<b>Oral</b>		
LD50	Rat	24 ml/kg

Components	Species	Test Results
	Wistar rat	24 g/kg 49 g/kg

\* Estimates for product may be based on additional component data not shown.

<b>Skin corrosion/irritation</b>	Causes skin irritation.
<b>Serious eye damage/eye irritation</b>	Direct contact with eyes may cause temporary irritation.
<b>Respiratory or skin sensitization</b>	
<b>Respiratory sensitization</b>	Not a respiratory sensitizer.
<b>Skin sensitization</b>	This product is not expected to cause skin sensitization.
<b>Germ cell mutagenicity</b>	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.
<b>Carcinogenicity</b>	This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.
<b>IARC Monographs. Overall Evaluation of Carcinogenicity</b>	
Not listed.	
<b>OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)</b>	
Not regulated.	
<b>US. National Toxicology Program (NTP) Report on Carcinogens</b>	
Not listed.	
<b>Reproductive toxicity</b>	Suspected of damaging fertility or the unborn child.
<b>Specific target organ toxicity - single exposure</b>	May cause drowsiness and dizziness.
<b>Specific target organ toxicity - repeated exposure</b>	Respiratory system. Skin. Central nervous system. Eyes. Peripheral nervous system. May cause damage to organs through prolonged or repeated exposure.
<b>Aspiration hazard</b>	May be fatal if swallowed and enters airways.
<b>Chronic effects</b>	May cause damage to organs through prolonged or repeated exposure.

## 12. Ecological information

**Ecotoxicity** Toxic to aquatic life with long lasting effects.

Product	Species	Test Results
11 OZ U-135A HI P LB 12PK		
<b>Aquatic</b>		
Algae	IC50	Algae 11111 mg/L, 72 Hours
Fish	LC50	Fish 10.2822 mg/L, 96 Hours
<b>Components</b>		
Cyclohexane (CAS 110-82-7)		
<b>Aquatic</b>		
Fish	LC50	Fathead minnow (Pimephales promelas) 23.03 - 42.07 mg/l, 96 hours
Isopropyl Alcohol (CAS 67-63-0)		
<b>Aquatic</b>		
Algae	IC50	Algae 1000.0001 mg/L, 72 Hours
Crustacea	EC50	Daphnia 13299 mg/L, 48 Hours
Fish	LC50	Bluegill (Lepomis macrochirus) > 1400 mg/l, 96 hours
n-Hexane (CAS 110-54-3)		
<b>Aquatic</b>		
Fish	LC50	Fathead minnow (Pimephales promelas) 2.101 - 2.981 mg/l, 96 hours

\* Estimates for product may be based on additional component data not shown.

**Persistence and degradability** No data is available on the degradability of this product.

### Bioaccumulative potential

**Partition coefficient n-octanol / water (log Kow)**

1,1-Difluoroethane 0.75

<b>Partition coefficient n-octanol / water (log Kow)</b>	
Cyclohexane	3.44
Isopropyl Alcohol	0.05
n-Hexane	3.9

**Mobility in soil** No data available.

**Other adverse effects** No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

### 13. Disposal considerations

<b>Disposal instructions</b>	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.
<b>Local disposal regulations</b>	Dispose in accordance with all applicable regulations.
<b>Hazardous waste code</b>	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
<b>Waste from residues / unused products</b>	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
<b>Contaminated packaging</b>	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers.

### 14. Transport information

#### DOT

<b>UN number</b>	UN1950
<b>UN proper shipping name</b>	Aerosols, flammable, (each not exceeding 1 L capacity)
<b>Transport hazard class(es)</b>	
<b>Class</b>	2.1
<b>Subsidiary risk</b>	-
<b>Label(s)</b>	2.1
<b>Packing group</b>	Not applicable.
<b>Special precautions for user</b>	Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling.
<b>Special provisions</b>	N82
<b>Packaging exceptions</b>	306
<b>Packaging non bulk</b>	None
<b>Packaging bulk</b>	None

This product meets the exception requirements of section 173.306 as a limited quantity and may be shipped as a limited quantity. Until 12/31/2020, the "Consumer Commodity - ORM-D" marking may still be used in place of the new limited quantity diamond mark for packages of UN 1950 Aerosols. Limited quantities require the limited quantity diamond mark on cartons after 12/31/20 and may be used now in place of the "Consumer Commodity ORM-D" marking.

#### IATA

<b>UN number</b>	UN1950
<b>UN proper shipping name</b>	Aerosols, flammable
<b>Transport hazard class(es)</b>	
<b>Class</b>	2.1
<b>Subsidiary risk</b>	-
<b>Label(s)</b>	2.1
<b>Packing group</b>	Not applicable.
<b>Environmental hazards</b>	Yes
<b>ERG Code</b>	10L
<b>Special precautions for user</b>	Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling.
<b>Other information</b>	
<b>Passenger and cargo aircraft</b>	Allowed with restrictions.
<b>Cargo aircraft only</b>	Allowed with restrictions.
<b>Packaging Exceptions</b>	LTD QTY

#### IMDG

<b>UN number</b>	UN1950
------------------	--------

Product name: HI-P CONTACT CLEANER

Product #: 1000012746 Version #: 08 Revision date: 03-06-2017 Issue date: 09-08-2015

SDS US  
8 / 11



<b>UN proper shipping name</b>	AEROSOLS
<b>Transport hazard class(es)</b>	
Class	2.1
Subsidiary risk	-
Label(s)	2.1
<b>Packing group</b>	Not applicable.
<b>Environmental hazards</b>	
Marine pollutant	Yes
<b>EmS</b>	F-D, S-U
<b>Special precautions for user</b>	Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling.
<b>Packaging Exceptions</b>	LTD QTY
<b>Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code</b>	Not applicable.
<b>DOT</b>	



IATA; IMDG



Marine pollutant



**General information**                      IMDG Regulated Marine Pollutant.

**15. Regulatory information**

**US federal regulations**                      This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

**TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)**

Not regulated.

**CERCLA Hazardous Substance List (40 CFR 302.4)**

Cyclohexane (CAS 110-82-7)

Listed.

n-Hexane (CAS 110-54-3)

Listed.

**SARA 304 Emergency release notification**

Not regulated.

**OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)**

Not regulated.

**Superfund Amendments and Reauthorization Act of 1986 (SARA)**

**Hazard categories**  
Immediate Hazard - Yes  
Delayed Hazard - Yes  
Fire Hazard - Yes  
Pressure Hazard - Yes  
Reactivity Hazard - No

**SARA 302 Extremely hazardous substance**

Not listed.

**SARA 311/312 Hazardous chemical** No

**SARA 313 (TRI reporting)**

Chemical name	CAS number	% by wt.
n-Hexane	110-54-3	20 - 40
Cyclohexane	110-82-7	0.1 - 1

**Other federal regulations**

**Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List**

n-Hexane (CAS 110-54-3)

**Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)**

1,1-Difluoroethane (CAS 75-37-6)

**Safe Drinking Water Act (SDWA)** Not regulated.

**US state regulations**

**US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)**

Not listed.

**US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))**

Isopropyl Alcohol (CAS 67-63-0)

Naphtha, (Petroleum), Hydrotreated Light (CAS 64742-49-0)

n-Hexane (CAS 110-54-3)

**US. Massachusetts RTK - Substance List**

1,1-Difluoroethane (CAS 75-37-6)

Cyclohexane (CAS 110-82-7)

Isopropyl Alcohol (CAS 67-63-0)

n-Hexane (CAS 110-54-3)

**US. New Jersey Worker and Community Right-to-Know Act**

1,1-Difluoroethane (CAS 75-37-6)

Cyclohexane (CAS 110-82-7)

Isopropyl Alcohol (CAS 67-63-0)

n-Hexane (CAS 110-54-3)

**US. Pennsylvania Worker and Community Right-to-Know Law**

Cyclohexane (CAS 110-82-7)

Isopropyl Alcohol (CAS 67-63-0)

n-Hexane (CAS 110-54-3)

**US. Rhode Island RTK**

1,1-Difluoroethane (CAS 75-37-6)

Cyclohexane (CAS 110-82-7)

Isopropyl Alcohol (CAS 67-63-0)

n-Hexane (CAS 110-54-3)

**US. California Proposition 65**

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

**US - California Proposition 65 - CRT: Listed date/Carcinogenic substance**

Benzene (CAS 71-43-2)

Listed: February 27, 1987

**US - California Proposition 65 - CRT: Listed date/Developmental toxin**

Benzene (CAS 71-43-2)

Listed: December 26, 1997

Toluene (CAS 108-88-3)

Listed: January 1, 1991

**US - California Proposition 65 - CRT: Listed date/Male reproductive toxin**

Benzene (CAS 71-43-2)

Listed: December 26, 1997

**International Inventories**

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

**16. Other information, including date of preparation or last revision**

**Issue date** 09-08-2015

**Revision date** 03-06-2017

**Version #** 08

**Disclaimer** The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. We cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.

**Revision information** Product and Company Identification: Alternate Trade Names